

THEOREM 5. (CHARACTERIZATION OF (s, ϕ) -FPS)⁸

Consider $s \in [0, \infty]$, a $[0, 1]$ -automorphism ϕ and an (s, ϕ) -FPS (P, I, J) on a set of alternatives A . Then the following equality holds

$$(P, I, J) = (R \cap_{\phi}^{\frac{1}{s}} \circ_{\phi} R^t, R \cap_{\phi}^{\frac{1}{s}} R^t, \circ_{\phi} R \cap_{\phi}^{\frac{1}{s}} \circ_{\phi} R^t)$$

with $R = P \cup_{\phi}^{\infty} I$.

6 Conclusion

We have described our itinerary in attempting to define, to construct and – above all – to characterise fuzzy preference structures. Various pitfalls had to be avoided, and only through the introduction of non-trivial conditions, fuzzy preference structures could finally be characterized. These fundamental results will undoubtedly foster the further development of both theory and applications of fuzzy preference modelling.

REFERENCES

1. B. De Baets, B. Van de Walle and E. Kerre, *A plea for the use of Lukasiewicz triplets in the definition of fuzzy preference structures. Part 2: The identity case*, Fuzzy Sets and Systems (1996), submitted.
2. J. Fodor and M. Roubens, *Fuzzy preference modelling and multicriteria decision support*, Kluwer, Dordrecht, 1994.
3. M. Frank, *On the simultaneous associativity of $F(x, y)$ and $x + y - F(x, y)$* , Aequationes Mathematicae 19 (1979), 194–226.
4. S. Ovchinnikov, *Modelling valued preference relations*, Multiperson decision making using fuzzy sets and possibility theory (J. Kacprzyk and M. Fedrissi, eds.), Kluwer, Dordrecht, 1990, pp. 64–70.
5. M. Roubens and Ph. Vincke, *Preference modelling*, Lecture Notes in Economics and Mathematical Systems 250, Springer-Verlag, Berlin, 1985.
6. B. Schweizer and A. Sklar, *Probabilistic metric spaces*, Elsevier, New York, 1983.
7. B. Van de Walle, B. De Baets and E. Kerre, *A plea for the use of Lukasiewicz triplets in the definition of fuzzy preference structures. Part 1: General argumentation*, Fuzzy Sets and Systems (1996), submitted.
8. B. Van de Walle, B. De Baets and E. Kerre, *Characterizable fuzzy preference structures*, European Journal of Operational Research (1996), submitted.

THE PROBLEM OF DEFINING NON DETERMINISTIC AGGREGATION OPERATORS

V. CUTELLO

Dept. of Mathematics
University of Catania
Catania, Italy

J. MONTERO

Dept. of Statistics and O.R.
Complutense University
Madrid, Spain

Some formalizations of physical or human decision processes must take into account some sort of non-determinism ("free will"). Such (generally complex) processes always contain some kind of aggregation procedures as building blocks. Thus, non-determinism is a problem that must be recognized and dealt with for aggregation operators. We will then introduce here the notion of non-deterministic aggregation operator. **Keywords:** Fuzzy Connectives, Fuzzy Sets, Aggregation Operators.

1 Introduction and Preliminaries

"The question of free will [...] is a real issue here, rather than an imagined one, but it is profound and hard to formulate adequately. The issue of determinism in physical theory is important, but [...] it is only part of the story." (see [10], pp.170). This quote from Penrose's famous book helps us introduce the motivation behind this paper. Many real-life problems are solved by means of some information aggregation procedures to be designed and used in an "intelligent" manner. In particular, we will follow here the formalizations of intelligent aggregation of information given and characterized by the authors in [3,4,6,9,7] (see also [11,12,18,14] for related work).

Information is passed to an aggregation operator as an ordered sequence of real numbers, which without loss of generality can be supposed to belong to the unit interval.

Aggregation operators are quite simple maps. Formally, an aggregation operator of dimension n , is any mapping

$$\phi : [0, 1]^n \rightarrow [0, 1].$$

We can also have hierarchical aggregations, that is to say aggregations of chunks of information which in turn represent aggregated information. The practical consequences of such hierarchical aggregations are quite interesting.

If we have aggregation maps of very big dimensions, hierarchical aggregations will allow us to deal with sub-aggregation operators of smaller dimensions, whose computational jobs can be parallelized. Thus, it will be possible to obtain a significant speed up of the whole aggregation process.

For instance, hierarchical aggregation procedures for individual preferences are defined by means of a basic classification of the individuals. The set of individual is divided into groups, in such a way that each individual is present in at least one of those groups. Then partial amalgamations of opinions within each group are to be amalgamated into one global amalgamation.

2 Non deterministic aggregation operators

Similarly to Turing Machine, a non deterministic aggregation operator is such that the same input can produce different outputs. For Turing Machine non determinism has the intended meaning of computational power: in one step the machine can non deterministically choose any of the possible outcomes. Non deterministic algorithms "guess" the best outcome among all possible ones.

Analogously, a non deterministic aggregation operator can be defined in the following way:

- we have a set M of mappings

$$\phi : [0, 1]^n \rightarrow [0, 1]$$

- and a non deterministic choice function (Turing Machine) η such that

$$\Phi(x_1, \dots, x_n) = \eta(\{\phi(x_1, \dots, x_n) | \phi \in M\})$$

Such aggregation operators will be denoted by $\Phi(M)$. Thus, by definition

$$\Phi(M)(x_1, \dots, x_n) = \eta(\{\phi(x_1, \dots, x_n) | \phi \in M\}).$$

For aggregation operators non determinism will have the intended meaning of "intelligence" power. We can think of it as a process that in one step tests all the possible operators of the family M and chooses the best one.

It is now quite natural to introduce the concepts of non-deterministic T-norms and T-conorms and OWA operators.

DEFINITION 1 A non deterministic T-norm is a non deterministic aggregation operator $\Phi(M)$ such that M is a set of T-norms.

Analogously, a non deterministic T-conorm is a non deterministic aggregation operator $\Phi(M)$ such that M is a set of T-conorms.

Finally, a non deterministic OWA operator is a non deterministic aggregation operator $\Phi(M)$ such that M is a set of OWA operators.

The above definitions clearly extend the traditional definitions which are obtained for $|M| = 1$. Moreover, we can characterize non deterministic aggregation operators as finite, discrete and continuous according to the cardinality of M .

In an extended version of this paper, we will comment upon such different families.

3 More on OWA operators.

A significative measure associated with OWA operators is the orness which estimates how close an OWA operator is to the max operator. It is defined as

$$\text{orness}(\phi) = \frac{1}{n-1} \sum_{i=1}^n (n-i)w_i.$$

Dual to the measure of orness is the measure of andness defined as $\text{andness}(\phi) = 1 - \text{orness}(\phi)$, which therefore measures how close an OWA operator is to the min operator.

How do we extend such definitions to non deterministic OWA operators? If we see the degrees of orness and andness respectively as degrees of optimism and pessimism, then we immediately have (for M finite)

$$\begin{aligned} \text{orness}(\Phi(M)) &= \max\{\text{orness}(\phi) | \phi \in M\} \\ \text{andness}(\Phi(M)) &= \min\{\text{andness}(\phi) | \phi \in M\} \end{aligned}$$

Therefore, likewise deterministic OWA operators, we have

$$\text{orness}(\Phi(M)) = 1 - \text{andness}(\Phi(M)).$$

If M is infinite, we substitute min and max with inf and sup and the result does not change.

4 Example

Very often in life we are faced with the problem of making a decision based on some imprecise knowledge. Typical cases of this kind occur in the medical field. In an emergency room of a hospital doctors have to decide whether or not to admit a patient in the hospital (see⁸). Their knowledge is what they have learned in Medical School (enriched by the experience gained at work) and the symptoms they observe in the patient. For instance, they may see that the patient "has a low fever", "is sweating a lot" and "feels a small pain in the

Moreover, it is possible that some of the predicates in \mathcal{P} are either unknown or analytically given and at the same time they can be either unconstrained or constrained to have values higher than a threshold α only within a given subset of U .

Given a set $F = \{\mu_1, \dots, \mu_n\}$ of membership functions associated to the predicates in \mathcal{P} , the fuzzy classification system (FCS for short) (4.1) is denoted by S_m^F . The notation S_n then denotes the collection of all possible FCS's S_m^F , which in turn can be characterized as the collection of all sets F of membership functions. Such FCS's are called *convex fuzzy classification systems*.

As proven in ¹, the membership functions in the system can be learned quickly from examples. However, we just use the min-max semantic. In real life, we know that the system semantic is not deterministic. Using our definition, we can extend such a system so to have

$$\tau \left(\bigvee_{j=1}^m \bigwedge_{i=1}^{n_j} Q_i^j(p_{Q_i^j}(x)) \right) = S_{j=1, \dots, m} (T_{i=1, \dots, n_j} (Q_i^j(p_{Q_i^j}(x)))) \quad (4.3)$$

where S and T are respectively a non deterministic T-norm and a non deterministic T-norm. The idea behind this extension is clear: during the inference process, the best logical aggregation operator from the classes S and T is non-deterministically chosen and applied.

As a consequence, an individual x is *justifiably classifiable* as a positive example for the concept C if

$$\tau \left(\bigvee_{j=1}^m \bigwedge_{i=1}^{n_j} Q_i^j(p_{Q_i^j}(x)) \right) > \theta$$

for some possible choices of the aggregation operators. Analogously, an individual x is *justifiably classifiable* as a negative example for the concept C if

$$\tau \left(\bigvee_{j=1}^m \bigwedge_{i=1}^{n_j} Q_i^j(p_{Q_i^j}(x)) \right) \leq \theta$$

for some possible choices of the aggregation operators.

5 Final Comments.

In an attempt to formalize free will and intelligence power in human decision processes we have introduced the notion of non deterministic aggregation operator. We think that such a notion brings closer theory to practitioners, i.e., to

the way practitioners solve in fact problems in real life: freely making decisions and justifying those decisions by means of their expertise (fuzzy membership functions) and global knowledge (aggregation rules).

Acknowledgment: This research has been partially supported by Dirección General de Investigación Científica y Técnica (Spain).

References

1. P. Bergadano, V. Cutello. Probably Approximate Correct (PAC) learning in fuzzy classification systems. *IEEE Transactions on Fuzzy Systems*, Vol.3 N. 4: 473-478, 1995.
2. A.M. Chang and L.O. Hall. The validation of fuzzy knowledge-based systems. In *Fuzzy logic for the management of uncertainty*, 589-604. L.A. Zadeh and J. Kacprzyk, editors. John Wiley and Sons, Inc., 1992.
3. V. Cutello and J. Montero. A characterization of rational amalgamation operations. *International Journal of Approximate Reasoning* 8:325-344 (1993).
4. V. Cutello and J. Montero. Hierarchies of intensity preference aggregations. *International Journal of Approximate Reasoning*, 10:123-133, 1994.
5. V. Cutello and J. Montero. Hierarchies of aggregation operators. *International Journal of Intelligent Systems*, 9:1025-1045, 1994.
6. V. Cutello and J. Montero. Hierarchical aggregation of OWA operators: basic measures and related computational problems. *Uncertainty, Fuzziness and Knowledge-Based Systems* 3:17-28 (1995).
7. V. Cutello and J. Montero. Information and aggregation: ethical and computational issues. In: D. Ruan, Ed., *Fuzzy Sets Theory and Advanced Mathematical Applications*. Kluwer, Boston (1995).
8. D.L. Hudson and M.E. Cohen. The role of approximate reasoning in a medical expert system. In *Fuzzy Expert Systems*, 165-179. A. Kandel, editor. CRC Press, 1991.
9. G.J. Klir and T.A. Folger. *Fuzzy sets, Uncertainty and Information*. Prentice Hall, Englewood Cliffs, NJ (1988).
10. R. Penrose. The Emperor's new mind. Concerning computers, minds and the laws of physics. Oxford University Press, 1989.

11. R.R. Yager. On ordered weighted averaging aggregation operators in multi-criteria decision making. *IEEE Transactions on Systems, Man and Cybernetics*, 18:183-190 (1988)
12. R.R. Yager. Families of OWA operators. *Fuzzy Sets and Systems*, 59:125-148 (1993)
13. R.R. Yager. MAM and MOM operators for aggregation. *Information Sciences*, 69:259-273 (1993)
14. R.R. Yager. Aggregation operators and fuzzy systems modeling. *Fuzzy Sets and Systems*, 67:129-145 (1994)

ON DEFINING AND COMPUTING FUZZY KERNELS ON \mathcal{L} -VALUED SIMPLE GRAPHS

R. BISDORFF

Centre de Recherche Public - Centre Universitaire, 162a av. de la Patencerie,
L-1511 Luxembourg, bisdorff@crpu.lu

M. ROUBENS

Institut de Mathématique, Université de Liège, 15, avenue des silleux-DI
S-4000 Liège, Belgium, roubens@math.ucl.ac.be

In this paper we introduce the concept of fuzzy kernels defined on \mathcal{L} -valued finite simple graphs in a sense close to fuzzy preference modelling. First we recall the classic concept of kernel associated with a crisp binary relation defined on a finite set. In a second part, we introduce \mathcal{L} -fuzzy binary relations. In a third part, we generalize the crisp kernel concept to such \mathcal{L} -fuzzy binary relations and in a last part, we present an application to fuzzy choice functions on fuzzy out-ranking relations.

1 Introduction

In this paper we introduce the concept of fuzzy kernel defined on \mathcal{L} -valued binary relations in a sense close to fuzzy preference modelling (cf. [5], [4]). First we introduce the concept of kernel associated to a crisp simple graph. In a second part we introduce in some detail \mathcal{L} -valued binary relations where \mathcal{L} is a symmetric evaluation domain for a credibility calculus introduced on binary relation. In a third part we generalize the kernel concept to such \mathcal{L} -valued simple graphs, that is \mathcal{L} -valued binary relations on finite sets and in a last part, we present the application to fuzzy choice functions on fuzzy out-ranking relations as used in the context of multicriterion decision aid (cf. [7]).

Let $G(A, R)$ be a simple graph with R being a crisp binary relation on a finite set A of dimension n . A subset Y_R of A is an *dominant (initial) or absorbent (terminal) kernel* of the graph G , if it verifies conjointly the following right and left interior stability and corresponding exterior stability conditions:

right interior stability:

$$\forall a, b \in A (a \neq b): ((a, b) \in R) \wedge (b \in Y_R) \Rightarrow (a \in Y_R).$$

left interior stability:

$$\forall a, b \in A (a \neq b): ((b, a) \in R) \wedge (b \in Y_R) \Rightarrow (a \in Y_R).$$

Intelligent Systems and Soft Computing for Nuclear Science and Industry

Proceedings of the 2nd International FLINS Workshop
Mol, Belgium, September 25-27, 1996

Edited by

Da Ruan, Pierre D'hondt and Paul Govaerts

Belgian Nuclear Research Centre

Etienne E. Kerre

University of Ghent, Belgium

Published by

World Scientific Publishing Co. Pte. Ltd.

P O Box 128, Farrer Road, Singapore 912803

USA office: Suite 1B, 1060 Main Street, River Edge, NJ 07661

UK office: 57 Shelton Street, Covent Garden, London WC2R 9NE

Library of Congress Cataloging-in-Publication Data
International FLINS Workshop (2nd : 1996 : Mol. Belgium)

Intelligent systems and soft computing for nuclear science and industry :

proceedings of the 2nd International FLINS Workshop, Mol. Belgium,

September 25-27, 1996 / edited by De Ruan . . . [et al.].

p. cm.

Includes bibliographical references and index.

ISBN 9810227388

I. Nuclear physics--Mathematics--Congresses. 2. Nuclear
engineering--Mathematics--Congresses. I. Ruan, Da. II. Title.

QC776 .I573 1996

621.4'8028563--dc20

96-23425

CIP

British Library Cataloguing-in-Publication Data

A catalogue record for this book is available from the British Library.

Copyright © 1996 by World Scientific Publishing Co. Pte. Ltd.

All rights reserved. This book or parts thereof may not be reproduced in any form or by any means, electronic or mechanical, including photocopying, recording or any information storage and retrieval system now known or to be invented, without written permission from the Publisher.

For photocopying of material in this volume, please pay a copying fee through the Copyright Clearance Center, Inc., 222 Rosewood Drive, Danvers, MA 01923, USA. In this case permission to photocopy is not required from the publisher.

This book is printed on acid-free paper.

Printed in Singapore by Ulu-Print

CONTENTS

Preface	xi
<i>D. Ruan, P. D'haeseleer, P. Govaerts and E. E. Kerre</i>	
Invited Opening Lecture	
Fuzzy Algorithmic and Knowledge-Based Decision Support in Nuclear Engineering	1
<i>H.-J. Zimmermann</i>	
PART 1: SOFT COMPUTING TECHNIQUES	9
On the Concept of a Linguistic Variable (Invited)	11
<i>E. E. Kerre</i>	
A Note on Mamdani Controllers	22
<i>B. De Baets</i>	
Minimization the Number of Rules in Fuzzy Relational Models	29
<i>I. G. Perfilova</i>	
Why Fuzzy Controllers Should Be Fuzzy	34
<i>A. Nowé</i>	
A Parallel Approach for the Automatic Generation of Fuzzy Systems	41
<i>L. Chan, X. Zhang and Y. He</i>	
The Fuzzy Control of Fully-Mechanized Coal Face Production Capacity	49
<i>E. Wang, Y. Weng and M. Wang</i>	
Self-Learning Fuzzy Logic Controllers Based on Reinforcement	55
<i>Z. Wang, S. Shao and J. Ding</i>	
The Simplifying Role of Pure and Stable Sets in Induced Possibilities and Necessities	60
<i>E. Tsiporkova</i>	
Fuzzy Metric Space and Its Completeness	70
<i>J. Hain and X. Zhang</i>	